



10-Port 10/100Mbps PoE Switch



SP5200-8PFE2FE

Key Features:

Ports: Provide 8*10/100Mbps PoE ports and 2 *10/100Mbps Uplink

PoE Standard: IEEE802.3af/at Power over Ethernet (PoE) Compliant

Total Power: Total power budget of 100W and 30W for all single PoE ports

Self-adaption: RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

Extend Mode: Extend PoE up to 250m on one single cable

Wide Application: Designed for Wifi AP and IP Security camera.VoIP etc

Surge protection: Protect the device from lightning surges and others electrical hazards

Considerate Design: Exquisite compact size with fanless design

Easy to use: Plug and play, No configuration required

Versatile PoE Port

Featuring 8* 10/100Mbps PoE ports which support IEEE802.3af/at standard and 2 * 10/100Mbps Uplink ports. the Benchu Group PoE switch provides Maximun power budget of 100W and 30W for single PoE ports sepectively,allowing users to have several different Networking products configured



Flexible Extend Mode

With the extend mode, the PoE Switch Series is able to offer more flexible choices for long range transmission, extending the distance up to 250m, which is greatly helpful to bring better user experience.

Surge Protection Design

Reaching 6KV surge protection, the PoE ports owns the capacity to keep the PoE Switch from lightning strikes and other electrical surges, offering more reliable performance even in some harsh environments.



SP5200-8PFE2FE

10-Port 10/100M PoE Switch


Technical Datasheet

Model	SP5200-8PFE2FE	
Hardware Specifications		
Network Connector	8*10/100BASE-T RJ45 auto MDI/MDIX ports	
	2*10/100BASE-T RJ45 auto MDI/MDIX ports	
PoE Port	8 10/100Mbps POE PSE port	
LED indicators	Power Indicator: PWR(green).	
	Network Indicator: Link(yellow)	
	PoE Working Indicator: PoE(green)	
Switch Architecture	Store and Forward	
Transmission model	IEEE802.3X full-duplex and Backpressure half-duplex	
Switch Performance	Backplane bandwidth	2.4Gbps
	Packet forwarding rate	1.49Mpps
	MAC address	4k
Power requirement	AC100-240V 50/60Hz	
ESD Protection	6KV ESD	
Dimension(W×D×H)	202mm x 140mm x 44.5mm(7.95in x 5.51in x 1.75in)	
Weight	<1.2Kg	
Power over Ethernet (PoE) Specifications		
Network standard	IEEE802.3i 10 BASE-T	
	IEEE802.3u 100 BASE-TX	
	IEEE802.3x Flow Control	
	IEEE802.3af Power over Ethernet	
	IEEE802.3at Power over Ethernet	
	IEEE802.3az EEE	
PoE Standard	IEEE 802.3af Power over Ethernet/PSE	
	IEEE 802.3at Power over Ethernet Plus/PSE	
PoE Supply Type	1/2(+), 3/6(-) End-span	
PoE Power Output	Per Port 52V DC, 300mA. max. 15.4 watts (IEEE 802.3af)	
	Per Port 52V DC, 600mA. max. 30 watts (IEEE 802.3at)	
PoE Power budget	100W	
Environment		
Safety	FCC Part15 Class A,CE,RoHs	
Environment specification	Operating temperature: -20℃~55℃， operating humidity: 5%~95%	
	Storage temperature: -20℃~75℃， storage humidity: 5%~95%	


SP5200-8PFE2FE

10-Port 10/100M PoE Switch


Interfaces



Structure Diagrams



Applications



Ordering Information

SP5200-8PFE2FE	10 Ports 10/100Mbps PoE switch , 6KV surge protection, IEEE802.3af/at
----------------	---